

1xN PM PLC Splitter

		Customer:
Spec. Number		
Date	2018-1-9	

Specifications

Parameter	Unit	Value				
Port Type		1x2	1x3	1x4	1x8	1x16
Operating Wavelength	nm	1310, 1550±40				
Insertion Loss	dB	≤4.0	≤6.8	≤7.4	≤10.7	≤13.9
Uniformity	dB	≤0.5	≤0.8	≤0.8	≤1.0	≤1.4
PER	dB	≥18	≥18	≥18	≥18	≥16
Directivity	dB	≥50				
Return Loss	dB	≥50				
Fiber Type		Panda fiber				
Operating Temperature	°C	-5~ +70				
Storage Temperature	°C	-40~ +85				

All the data above does not include connectors

Package Dimensions

Pigtail Type	1x3, 1x4, 1x8	1x16
Steel tube	60x7x4	60x12x4

Ordering Information

PMPL C	Wavelength range	ports	Package Type	Pigtail Type	Length	Connector
	1310=1310 1550=1550	02=1x2 04=1x4 06=1x6 08=1x8 12=1x12 16=1x16 24=1x24	1=60x7x4 2=60x7x4 3= 60x12x4	0= Ribber fiber 1=250um Bare fiber 2=900um loose tube	H=0.5m 7=0.7m 1=1.0m S=Specify	0=None 1=FC/UPC 2=FC/APC 3=SC/APC 4=SC/UPC 6=LC/PC 7=LC/APC